PANZERI

Planet Ring

220-240V AC dimmable (DALI/Push DIM)


X08301.040.0402

white



Data sheet

CODE	X08301.040.0402
SYSTEM POWER CONSUMPTION	28W
EFFICACY	78.54lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3321lm
LUMEN OUTPUT	2199lm
EFFICIENCY	66.2%
WEIGHT	4,12 Kg
PROTECTION DEGREE	IP40 IP20
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	46,0 x 18,0 x 46,0 cm



Pickled sheet metal closing frame in polyacrylic paint. Modelled polycarbonate diffuser with opaline finish. Galvanized sheet metal brackets for false ceiling fixing. Built-in hole dimension: Ø 415mm (Ø 16,3")










Technical drawing





Polar diagram

