


## Hilow Line

220-240V AC dimmer on cable

T10819.200.0522

 mat brass



### Data sheet

CODE	T10819.200.0522
SYSTEM POWER CONSUMPTION	39W
EFFICACY	69.59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmer on cable
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4032lm
LUMEN OUTPUT	2714lm
EFFICIENCY	67.3%
WEIGHT	10,16 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 222,0 x 13,0 cm



Floor lighting fixture for interiors, with indirect light emission.  
 Bearing base in white travertine marble.  
 Extruded aluminium structure in bronze or mat brass polyacrylic paint.  
 Die-cast aluminium end caps in polyacrylic paint.  
 Extruded polycarbonate diffuser with opaline finish.  
 Equipped with a 3m (118,1") long power cable with switch to adjust luminosity and plug.



### Technical drawing

