# BORGO 43 2700K **7543**

# astro





## PRODUCT SPECIFICATION

#### **GENERAL**

FINISH: Textured White CABLE LENGTH: Not Applicable Metal - Stainless Steel MAIN MATERIAL: **GROSS WEIGHT:** 0.36 (Kg) **DIMENSIONS:** H: 133mm W: 43mm D: 78mm CLASS: CE (Class III) INSTALLATION ORIENTATION: Wall Mount - Vertical IP65 IP RATING:

INSTALLATION ORIENTATION: Wall Mount - Vertical IP RATING: IP65

CUT OUT HOLE: L: 100mm W: 30mm BATHROOM ZONE: Zone 1, 2, 3

RECESS DEPTH: 75 (mm) VOLTAGE: Constant Current 350 (mA)

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

### LAMP

LIGHT SOURCE:High Power LEDMACADAM ELIPSE:3-StepMAXIMUM WATTAGE:1WUGR:To Be AdvisedMAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:Not ApplicableLAMP INCLUDED?Yes (Integral)TILT ADJUSTMENT ANGLE:Not Applicable

LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable
LUMINOUS FLUX: 12.2 (Im) ROTATION ADJUSTMENT ANGLE: Not Applicable
COLOUR TEMP: 2700 (K) AVERAGE LIFESPAN: 60,000 (Hrs)
CRI: 80 L70: >60,000 (Hrs)

**R9:** 9.0

### **ELECTRICAL**

SWITCHED: SUPPLY FREQUENCY: No Not Applicable DIMMABLE: Yes DRIVER/BALLAST VOLTAGE: Not Applicable DIMMING METHOD: Control Gear Dependant DRIVER AVERAGE LIFESPAN: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable **EFFICACY:** 4.69 (lm/W)

DRIVER OUTPUT CURRENT:Not ApplicableEFFICACY:4.69 (lm/W)DRIVER OUTPUT VOLTAGE:Not ApplicableDRIVER/BALLAST INCLUDED?Not applicable

## ADDITIONAL INFORMATION



BOX QUANTITY x 24

Œ











