# **PANZERI**

## Jackie lot

220-240V AC dimmable (IoT/Step DIM)

A07702.000.0413





#### Data sheet

CODE	A07702.000.0413
SYSTEM POWER CONSUMPTION	10W
EFFICACY	70.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	90°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (IoT/Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	884lm
LUMEN OUTPUT	706lm
EFFICIENCY	79.9%
WEIGHT	0,47 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm



Wall lighting fixture for interiors, with swivelling light beam.

Pickled sheet metal wall bracket in polyacrylic paint.

Die-cast aluminium wall plate in polyacrylic paint.

 $\label{thm:continuous} \mbox{Die-cast aluminium structure in white, black, red or titanium polyacrylic paint.}$ 

Die-cast aluminium head rotating on two axes in polyacrylic paint. Modelled acrylic diffuser with mat finish and double serigraphy.

Push-button to adjust luminosity according to 5 levels of visual comfort.


 $\label{lem:module for luminous flux automatic regulation, complete with sensor for measuring} \\$ environmental conditions and with Bluetooth antenna for managing the device or for connecting it to a Building Automation system.








### **Technical drawing**



## Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270