# **PANZERI**

## Murané R

24V DC

M11606.110.0410





#### Data sheet

CODE	M11606.110.0410
SYSTEM POWER CONSUMPTION	62W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	3000lm
WEIGHT	10,30 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm











Single or multiple suspension lighting fixture for interiors, with direct and indirect light

Bended extruded aluminium structure in champagne or mat black polyacrylic paint.

Pickled sheet metal cover in polyacrylic paint.

Turned brass wiring supports.

Diffusers in blown glass with bronze colour.


Turned aluminium closing disks in polyacrylic paint.

Provided without suspension kit, power cable and canopy.

#### Technical drawing







### Polar diagram

## **PANZERI**

### Murané R

#### Accessories / power supply and fixing

YFA11600.010

 $Multiple\ power\ supply\ and\ suspension\ kit\ with\ 20cm\ (7,9")\ long\ power\ cable\ and\ 8cm\ (3,1")\ long\ steel$ 

CE EHE 🗵







YFA11600.025

Multiple power supply and suspension kit with 30cm (11,8") long power cable and 27cm (10,6") long steel cables.







YFR11606.075.A02







Power supply and suspension kit with champagne or mat black canopy, 75W DALI/Push DIM dimmable driver, 5m (196,9") long power cable, griplocks and 5m (196,9") long steel cables. Canopy for power supply up to  $1\,M116_{--}080.0410$  or  $1\,M116_{--}110.0410$  model.



YFR11606.180.A02







Power supply and suspension kit with champagne or mat black canopy, 180W DALI/Push DIM dimmable driver, 5m (196,9") long power cable, griplocks and 5m (196,9") long steel cables. Canopy for power supply up to  $3\,M116\_.080.0410$  or  $2\,M116\_.110.0410$  models maximum.

