

F50




matt white

MINI INCASSO IN BATTUTA CON DIAMETRO 35 mm.

Una luce puntuale che definisce gli spazi. F50 è un incasso da interni per installazione in parete e soffitto di cartongesso, disponibile con finitura bianca, in grado di inserirsi nelle superfici. Essenziale e deciso, è una fonte di luce pura, per un risultato inconfondibile.

MINI RECESSED LUMINAIRE WITH A DIAMETER OF 35 mm.

A punctual light which defines spaces. F50 is a recessed indoor luminaire installable on plasterboard walls and ceilings and available with white finishings. It is a product which perfectly integrates itself with the surfaces it applies to. Sharp and essential, it is a pure source of light which gives a unique effect.



CODE COMPOSITION

1022 WH 2 R 00 E _ WD

light colour

27	2700K
30	3000K

example of code composition 1022 WH 2 R 00 E 30 WD

TECHNICAL FEATURES

Code	1022 XX
Type	Downlight 90° Wall recessed 90°
Material	Aluminum
Finishing	White
Weight	0.04 Kg
Mounting	Wall and ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Constant current electronic driver (not included)
Cut out for plasterboard	Ø 32 mm
Lamp type	LED Vf: 3 VDC
Lamp wattage	1W - 350mA 2W - 500mA
Luminous efficacy	75 lm - 3000K - 350mA 170 lm - 3000K - 500mA
Light distribution	Wide beam 120°
Fitting	-
Light colour	White 3000K White 2700K (on request)
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Note	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1022 XX	H8350	Constant current electronic driver	Suitable for n°1 code 1022 XX - 350 mA
	H8500.B	Constant current electronic driver. Remote installation	Suitable for n°5 code 1022 XX - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°2 code 1022 XX - 500 mA

