



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|----------------------------------|------------------------|--|
| FINISH: | Polished Chrome | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Zinc | GROSS WEIGHT: | 1.86 (Kg) |
| DIMENSIONS: | H: 500mm W: 90mm D: 59mm | CLASS: | CE (Class II) |
| INSTALLATION ORIENTATION: | Wall Mount - Horizontal/Vertical | IP RATING: | IP44 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 2, 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materials |

LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | LED Strip | MACADAM ELLIPSE: | +/- 100K |
| MAXIMUM WATTAGE: | 20.3W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 858 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 3000 (K) | AVERAGE LIFESPAN: | 50,000 (Hrs) |
| CRI: | 80 | L70: | Not Applicable |
| R9: | 7.0 | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|---------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | 47 - 63 (Hz) |
| DIMMABLE: | No | DRIVER/BALLAST VOLTAGE: | 90-264 VAC (V) |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | 20,000 (Hrs) |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | 42.27 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | 12 (V) | DRIVER/BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION



BOX QUANTITY x 9

PRODUCT ELEVATIONS

