

PANZERI

Gonio

220-240V AC dimmable (DALI/Push DIM)

A01902.030.0402

● black



Data sheet

CODE	A01902.030.0402
SYSTEM POWER CONSUMPTION	26W
EFFICACY	86.62lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3240lm
LUMEN OUTPUT	2252lm
EFFICIENCY	69.5%
WEIGHT	1,08 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 35,0 x 10,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission.


Pickled sheet metal wall bracket in polyacrylic paint.

Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded acrylic diffusers with opaline finish.

Die-cast aluminium end caps in polyacrylic paint.

Technical drawing



Polar diagram



cd/klm
— C0 - C180 - - - C90 - C270