

ENNA SURFACE 7499

SKU 1058027

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Black	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.6 (kg)
DIMENSIONS:	H: 110mm D: 155mm Ø: 80mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Wall Mount - Vertical	IP RATING:	IP20
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	High-Power LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	1 x 3W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	To Be Advised
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	90 (Degrees)
LUMINOUS FLUX:	To Be Advised	ROTATION ADJUSTMENT ANGLE:	330 (Degrees)
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	54,000 (Hrs)
CRI:	85	L70:	To Be Advised
R9:	To Be Advised		

ELECTRICAL

SWITCHED:	Yes	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	60,000 (Hrs)
DRIVER OUTPUT CURRENT:	700 (mA)	EFFICACY:	To Be Advised
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION

CE



BOX QUANTITY X12

PRODUCT ELEVATIONS

