PANZERI

Тоу

220-240V AC dimmable (DALI/Push DIM) A01621.045.0402

Data sheet

CODE	A01621.045.0402
SYSTEM POWER CONSUMPTION	24W
EFFICACY	73.13lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2732lm
LUMEN OUTPUT	1755lm
EFFICIENCY	64.2%
WEIGHT	1,61 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 13,0 x 64,0 cm




Wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal structure in polyacrylic paint. Aluminium dissipation plates. Pickled sheet metal cover in white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or in polished or mat stainless steel.

Flat frosted glass diffusers.

gold leaf



Technical drawing



Polar diagram

