


Q1 48V



CODE COMPOSITION

T048 L 00005		0
<i>dimmiability</i>		
ND	non dimmable	
DA	DALI	
11	1-10V	
<i>light colour</i>		
27	2700K	
30	3000K	
40	4000K	
<i>lens</i>		
12	12°	
24	24°	
38	38°	
<i>finishing</i>		
W1	white	
B1	black	

example of code composition T048 L 00005 **W1 12 27 ND 0**

TECHNICAL FEATURES

Code	T048 L 00005 XX
Type	Projector ± 360° / ± 90°
Material	Aluminum
Finishing	White Black
Weight	0.8 Kg
Mounting	Track 48V
IP rating	IP40
Insulation class	III
Control gear	Electronic driver on board (included)
Lamp type	LED
Lamp wattage	1 x 12W
Luminous efficacy	1550 lm - 3000K
Light distribution	Beam 24° Beam 12° 38° (on request)
Light colour	White 3000K White 2700K White 4000K (on request)
Voltage connection	48 VDC
CRI	>90
Note	-

Proiettore per binario 48V ad alte performance in alluminio verniciato a polvere: Q1 48V è un apparecchio per interni che garantisce il minimo impatto visivo. Completamente orientabile a 360°, è disponibile in più varianti ottiche. Il proiettore Q1 48V ha sorgente luminosa a LED (COB) CRI 90, 3000K o 2700K (4000K su richiesta) alimentata in corrente continua con convertitore a scomparsa collocato all'interno del binario.

48V track projector with high performances in powder varnished aluminium Q1 48V is a fitting for interiors which guarantees minimum visual impact. 360° completely adjustable. It is available in a variety of optics. The Q1 48V projector has an LED (COB) CRI >90, 3000K or 2700K light source (4000K on request) fed in direct current with incorporated convertor located inside the track adaptor.

