# **PANZERI**

## To-be

220-240V AC ON-OFF

P02701.045.1701





#### Data sheet

CODE	P02701.045.1701
SYSTEM POWER CONSUMPTION	10W
EFFICACY	80.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	35°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	806lm
LUMEN OUTPUT	806lm
EFFICIENCY	100%
WEIGHT	0,85 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,5 x 45,0 x 10,5 cm



Ceiling lighting fixture for interiors, with direct light emission.

 ${\sf Extruded\ aluminium\ structure\ in\ white,\ mat\ black,\ bronze\ or\ mat\ brass\ polyacrylic\ paint}$ or with gold leaf coating.

Pickled sheet metal wiring support brackets in polyacrylic paint.

Anodized extruded aluminium heat sink.

Reflector in thermoplastic material with chrome plated finish.


Transparent polycarbonate screen.








## Technical drawing



## Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270