




401012

TECH MEDIUM 01 ROUND

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 10° | 720 | 90.33 |
| high-power led | 30° | 684 | 85.50 |
| high-power led | 45° | 650 | 81.25 |
| 4000°K neutral-white | | | |
| high-power led | 10° | 750 | 93.75 |
| high-power led | 30° | 713 | 89.13 |
| high-power led | 45° | 677 | 84.63 |

Finish color options:



Technical features



Technical data

| | |
|----------------|---|
| Wattage | 8 WATT |
| IP Rating | IP65 |
| IK Rating | IK09 |
| Material | High corrosion resistance die-cast copper-free aluminium body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | NR. 5 x 1.5W CREE "XP-G3" LED down. |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Rubber grommet | M20 Rutaseal® in EPDM |
| Glass | Tempered |
| Gross weight | 3,00 Kg |

