## ideal lux. Park Led

## DOWNLIGHT


Inox steel 316 body. Transparent tempered glass. Walkable. Integrated LED source. Absence of visible screws. Protection degree IP68. Two versions available with formwork of different heights for higher installation versatility.







Code	222875
Item name	PARK LED PT1 4.8W 60°
Insulation class	Class III
IP	68
Power	LED 4,8W   450 Lm
Bulb   LED included	4000K   50.000 h
Net Weight	1,260 Kg
Volume	0,0054 m³
Base / Hole	ø 8,8 cm



IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel. +39 041 5790500, Fax +39 041 8872349, E-mail info@ideal-lux.com www.ideal-lux.com

## ideal lux. Park Led



11111 LAV 60.24

en en et

Code Item name Power Measure 226187 PARK LED DRIVER 20W ON-OFF 20W 118 x 26 x 35 mm



226194 PARK LED DRIVER 35W ON-OFF 35W 148 x 30 x 40 mm

Code Item name Power Measure 226200 PARK LED DRIVER 100W ON-OFF 100W 220 x 39 x 68 mm

Code Item name Power Measure 226217 PARK LED DRIVER 185W ON-OFF 185W 220 x 39 x 68 mm



IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel. +39 041 5790500, Fax +39 041 8872349, E-mail info@ideal-lux.com www.ideal-lux.com