FLEXALIGHTING
TOP QUALITY ITALIAN LED LIGHTING

NONE R2
Trimless downlights

IP44 made in Italy

design Roberto Mantovani



The None range of trimless, recessed fixtures offers extremely bright 5° light beams. The extremely thin edge and recessed optics make it an innovative and effective element, able to offer effective lighting solutions.

La gamma di incassi trimless None offre fasci luminosi di 5° di estrema pulizia. Il bordo estremamente ridotto e l'ottica arretrata ne fanno un elemento innovativo ed efficace, capace di offrire soluzioni luminose efficaci.

La gamme d'encastrables trimless None propose des faisceaux lumineux de 5° d'une propreté extrême. Le bord extrêmement réduit et l'optique en retrait en font un élément innovant et efficace, capable d'offrir des solutions lumineuses efficaces.

Die Trimless Einbauleuchten None bieten extrem saubere 5°-Lichtverhältnisse. Die extrem reduzierte Kante und die Rückwärtsoptik machen es zu einem innovativen und effektiven Element, das in der Lage ist, effektive Beleuchtungslösungen anzubieten.

La gama de luminarias empotrables trimless None ofrece haces luminosos de 5° extremadamente sutiles. El borde extremadamente reducido y la óptica hacia atrás lo convierten en un elemento innovador y eficaz, capaz de ofrecer soluciones de iluminación eficaces.

Supply current
350-500mA (V_f 2,9V)

Power
1-2W

Series wiring

Dimensions



Photometric diagrams



CCT/CRI/Flux

	350mA	500mA
2700K	89lm	128lm
3000K	93lm	133lm
4200K	103lm	154lm
6000K	114lm	165lm

Code construction

NRS X X 5

Beam angle 5°

0	1	2	3	6	7	8
2700K	3000K	4200K	6000K	Blue	Green	Red

1	5
White	Black

Optionals

ZQC001 White **ZQC001B** Black
Plasterboard recessing frame



AL7022
24VDC/500mA constant current converter

Drivers

350 mA

on/off	dimmable
AL1034 (1..11) 30mm IP20	**AL4000** (1..12) 72mm IP20 PUSH 1..10V
AL1035 (1..11) 40mm IP20	**AL4051** (1..12) 72mm IP20 DALI
AL1037 (1..16) 55mm IP20 S.P.	**AL4053** (1..12) 60mm IP20 IGBT-TRIAC
AL9011 (1..12) 60mm IP67	

500 mA

on/off	dimmable
AL1074 (1..7) 30mm IP20	**AL4010** (1..12) 72mm IP20 PUSH 1..10V
AL1077 (1..6) 40mm IP20	**AL4151** (1..12) 72mm IP20 DALI
AL1084 (1..11) 55mm IP20 S.P.	**AL4153** (1..12) 60mm IP20 IGBT-TRIAC
AL9051 (1..10) 60mm IP67	

FLEXALIGHTING Srl via Lisbona 21, 50065 Pontassieve (FI) Italy t. +39.055.8323021 f. +39.055.8324866 info@flexalighting.it