


















technics	  <p>profile dolma 80 outdoor</p>		  <p>minimal cut-out</p>		Name	Reference	l x w x h	Min. cut-out L x W x H
					Dolma 80 Outdoor	kr715903	120 x 105 x H	125 x 110 x profile length +20mm
1 dimensions					<div>Please make sure that mains voltage is disconnected before proceeding!</div>  !! For security reasons: do not connect (mains) voltage until final installation is done!!			
2 installation	in case of stonework or concrete (see*)  <p>provide a gap with minimal cut-out</p>		 <p>assemble the installation brackets</p>  <p>intersection</p>		 <p>provide main cable in the profile and place profile in the gap (see*)</p>			
installation			 <p>use installation-brackets to line the profile vertical and to align in the center of the gap</p>		 <p>to secure the profile use glue-kit or an equal on several points (don't use foam or anything that thickens!!!)</p>			
installation	 <p>remove installation-brackets when glue is dried</p>		 <p>fill gaps and finish the surface with corresponding material used</p>		 <p>place click-in profile and remove plastic from cover</p>			




use shrink sleeves to make connection with main power supply, heat the shrink sleeve with a heat gun or lighter untill the sleeve shrinks around the cable.

Name	Reference	Voltage ⚡
Dolma 80 Outdoor	kr91590x	230V/12V
Dolma 80 Outdoor	kr91599x	230V/1,5kV
Dolma 80 Outdoor	kr91595x	230V
Dolma 80 Outdoor	kr91596x	230V

3 connection



caution: do not make contact with isolation material



caution: make sure water conduit is placed below the profile

caution in regards to installation:

- in case of reinforced concrete, recalculate the construction
- place profile minimum 10mm above groundfloor
- make sure the connection is done in the profile

caution in regards to watertightness

- the profile is IP40, the module is IP55
- in case of installation in damp environments (e.g. shower or bathroom) please request a special from Kreon and place gear on remote.

4 * caution



5 pictures

kreon nv

Industrieweg Noord 1152
3660 Opglabbeek
Belgium

Tel + 32 89 81 97 80
Fax + 32 89 81 97 90

www.kreon.com
mailbox@kreon.be

Rev. date : 14/02/2017
KR8159001439