



## 602201



400mm height bollard, for outdoor installation, 360° light distribution, phospho-chromatised and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.




Ø 70 mm





## **Technical data**

Wattage	20 WATT		
IP Rating	IP66		
IK Rating	IK09		
Material	High corrosion resistance extruded copper-free aluminum head and extruded pole		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light Source	NR. 24 x CREE "XH-G" LED		
Screws	Stainless steel		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Gasket	Silicone rubber		
Glass	Tempered		
Cable gland	PG11		
Power cable	1,5 meters power cable included		
Gross weight	3,00 Kg		





light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
mid-power led	•	radial 360°	1.600	80.00
4000°K neutral-white				
mid-power led	•	radial 360°	1.650	82.50

Finish color options:

Textured Grey RAL 9006

400 | puk.it

Anthracite Grey RAL 7016 Matt Black (on request)

\_\_\_\_\_

AC065 ANCHORAGE UNIT FOR ALDER SERIES

