

PANZERI

Line

220-240V AC ON-OFF

T03621.000.0401

 gold leaf

INDIRECT
LIGHT

Data sheet

CODE	T03621.000.0401
SYSTEM POWER CONSUMPTION	10W
EFFICACY	85.4lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	854lm
LUMEN OUTPUT	854lm
EFFICIENCY	100%
WEIGHT	10.62 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Floor lighting fixture for interiors, with indirect light emission.
Pickled sheet metal bearing base in white, black, mat brass or titanium polyacrylic paint, or with gold leaf coating.
Structure in tapered steel tube in white, black, mat brass or titanium polyacrylic paint, or with gold leaf coating.
Anodized extruded aluminium heat sink.
Reflector in thermoplastic material with chrome plated finish.
Transparent polycarbonate screen.
Equipped with a 2,3m (90,6") long power cable in transparent PVC with switch and plug.

Technical drawing

