

FOCUS




INCASSO CON VETRO RETROCESSO E FORME SINUOSE.

Un prodotto che delinea la strada dell'architettura contemporanea, con le sue linee pulite e il design geometrico: Focus, un apparecchio da interni, un incasso a scomparsa totale per installazione a soffitto di cartongesso o laterizio. Il prodotto scompare, per dare spazio solo al fascio luminoso, che illumina, evidenzia e arreda gli spazi in cui viene installato. Il corpo di Focus è realizzato in AirCoral®, per una perfetta combinazione di design e tecnologia all'avanguardia, attenta all'ambiente e alla qualità dell'aria che respiriamo.

RECESSED FITTING WITH REAR GLASS AND SINUOUS SHAPES.

Outlining the path of contemporary architecture, with its clean lines and geometric design: through its light Focus, a totally disappearing indoor recessed luminaire, installable on plasterboard or brick ceilings.
This product disappears, in order to give way to the light beam alone, which lights up, points out and decorates the spaces it is installed in.
The body of Focus is made of AirCoral®, for a perfect combination of design and cutting-edge technology, with particular attention to the environment and air quality.



TECHNICAL FEATURES

Code	6163.Z.AC	6169.Z.AC	6161.AC	6162.AC
Type	Downlight 90°	Downlight 90°	Downlight 90°	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	4.05 m²	4.05 m²	4.05 m²	4.05 m²
Weight	1.8 Kg	2.3 Kg	1.7 Kg	1.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40	IP40
Insulation class	III	III	III	I
Control gear	Constant current electronic driver (not included)	Constant current electronic driver	Electronic transformer (not included)	-
Dimensions	A: 140 mm	A: 140 mm	A: 120 mm	A: 120 mm
Cut out for plasterboard	155 x 155 mm	155 x 155 mm	155 x 155 mm	155 x 155 mm
Lamp type	LED 500 mA ⚡ Vf: 18 VDC	LED 500 mA ⚡	QR CB 51 ⚡	QPAR 16 ⚡
Lamp wattage	1 x 9W	1 x 9W	1 x 50W max	1 x 50W max
Luminous efficacy	1125 lm - 3000K	1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	Wide beam 40°	-	-
Fitting	-	-	GU5.3	GU10
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)	-	-
Light hole	90 x 90 mm	90 x 90 mm	90 x 90 mm	90 x 90 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz	By driver (optional)	220-240V / 12V · 50/60Hz
CRI	>90	>90	-	-
Emergency	-	1 hour	-	-
Energy efficiency class	A++	A++	A	A
Note	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling. On request available dimmable PUSH or DALI.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.

OPTIONAL ACCESSORIES

product code	optional code	description	info
6163.Z.AC	H8500.E	Constant current electronic driver	Suitable for n°2 code 6163.Z.AC - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 6163.Z.AC - 500 mA
	BR6163LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6161.AC	H8060.LED	Dimmable electronic transformer	Max watt 60W Volts · Hz 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	Bulb 7W · 12V
	BR6161LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6162.AC	0009KIT	Kit LED dimmable	Bulb 6W · 220-240V
	BR6162LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²