



## General info

### Indoor - Ceiling lamps

|              |                              |
|--------------|------------------------------|
| Ean          | 8021696328096                |
| Item         | GEMINI PL D081 ON-OFF OTTONE |
| Installation | Ceiling lamps                |
| Guarantee    | 5 years                      |
| Gross weight | 7.55 kg                      |
| Volume       | 0.088752 m³                  |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 4.55 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | NO, On-Off                                                                     |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 41 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 41,00 W                               |
| Features LED           | LED SMD                                   |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 30000 h                                   |
| CRI                    | > 80                                      |
| Light beam             | -                                         |
| Light beam flux        | 5400 lm                                   |
| Useful light flux      | 2350 lm                                   |
| Photobiological risk   | 2                                         |