

CORE 6

Recessed optics downlights

design Lapo Grassellini



The Core recessed fixtures range matches the utmost performance to incredible compactness. Recessed optics ensure high visual comfort. Revolutionary in dissipative, functional design, it offers the possibility to combine colour temperatures and beam angles in CRI85 and CRI93 and CRI98 with R9 93 versions.

La gamma di incassi Core combina altissime prestazioni ad una dimensione incredibilmente contenuta. L'ottica arretrata garantisce un alto comfort visivo. Rivoluzionari per il design funzionale alla dissipazione, offrono la possibilità temperature colore ed aperture di fascio nelle versioni a CRI85 ed a CRI93 e CRI98 con R9 93.

La gamme d'encastrables Core associe prestations très élevées et dimension incroyablement contenue. L'optique en retrait garantit un confort visuel élevé. Révolutionnaires pour le design fonctionnel à la dissipation, ils offrent la possibilité de températures, couleur et ouvertures de faisceau dans les versions à CRI85 et à CRI93 et CRI98 avec R9 93.

Die Einbauleuchtenserie Core vereint höchste Leistung mit einer unglaublich kleinen Größe. Die Rückwärtsoptik garantiert hohen Sehkomfort. Revolutionär in ihrem funktionalen Design zur Dissipation, bieten sie die Möglichkeit, Temperaturen, Farben und Strahlöffnungen in den Versionen CRI85 und CRI93 und CRI98 mit R9 93 zu kombinieren.

La gama de luminarias empotrables Core combina un rendimiento muy alto con un tamaño increíblemente pequeño. La óptica hacia atrás garantiza un alto confort visual. Revolucionarios por el diseño funcional para la disipación, ofrecen la posibilidad de temperaturas de color y aperturas de haz en las versiones CRI85 y CRI93 y CRI98 con R9 93.



IP44 made in Italy

Supply current


500mA (V_i 9V)

Power


6W

Series wiring

Dimensions




Photometric diagrams



CCT/CRI/Flux

CCT	CRI	Flux
2700K	CRI98	540 lm
3000K		600 lm
4000K		620 lm

Code construction



Optionals

L001 Low luminance louver

SC1001 Milky screen

Note: the filter and the screen must be ordered together with the lighting fixture

AL7022 24VDC/500mA constant current converter

Drivers

