

BARD



INCASSO IN BATTUTA
COMPLETAMENTE VERNICIABILE COME IL SOFFITTO.

Bard è un apparecchio da incasso per installazione in battuta su soffitti di cartongesso, è dotato di corpo in Coral® e una meccanica composta da molle che permettono di fissarlo al controsoffitto. Con un corpo esterno a base quadrata di 100 x 100mm e un'anima interna metallica che, effettuando un foro di Ø 85 mm, permette installazioni su qualsiasi tipo di supporto. Bard è un apparecchio da interni dal design minimale e disponibile con diverse sorgenti luminose LED.

RECESSED TILL END POSITION
COMPLETELY PAINTABLE LIKE THE CEILING.

Bard is a recessed luminaire installable on plasterboard ceilings, equipped with a Coral® body and a spring mechanism that allows the product to be fixed to the false ceiling. Square base outer body measuring 100 x 100mm and inner metal core which, installed inside a Ø 85 mm hole, can be installed on any type of support. Bard is an indoor luminaire with a minimal design, available with different LED luminous sources.

CODE COMPOSITION

1005.00 6 R 00 E 00 WD


1006.00 6 R 00 E 00 WD

TECHNICAL FEATURES

| Code | 1005.00 XX | 1006.00 XX |
|--------------------------|--|---|
| Type | Downlight 90°  | Downlight 90°  |
| Material | 00: Coral® | 00: Coral® |
| Weight | 0.7 Kg | 0.7 Kg |
| Mounting | Ceiling recessed | Ceiling recessed |
| IP rating | IP20 | IP20 |
| Insulation class | III | I |
| Control gear | Electronic transformer (not included) | - |
| Cut out for plasterboard | Ø 85 mm | Ø 85 mm |
| Lamp type | QR CB 51 LED (optional)  | QPAR 16 LED (optional)  |
| Lamp wattage | - | - |
| Luminous efficacy | - | - |
| Light distribution | - | - |
| Fitting | GU5.3 | GU10 |
| Light colour | - | - |
| Light hole | Ø 50 mm | Ø 50 mm |
| Voltage connection | By driver (optional) | 220-240V · 50/60Hz |
| CRI | - | - |
| Emergency | - | - |
| Energy efficiency class | A | A |
| Note | - | - |

OPTIONAL ACCESSORIES

| product code | optional code | description | info |
|--------------|----------------------|---|--|
| 1005.00 XX | H8060.LED 0008KIT | Dimmable electronic transformer Kit LED dimmable | Max watt 60W Volts · Hz 230/12V · 50/60Hz Bulb 7W · 12V |
| 1006.00 XX | 0009KIT | Kit LED dimmable | Bulb 6W · 220-240V |



CODE COMPOSITION

1004.00 4 R 40 E _ WD

light colour

| | |
|----|-------|
| 27 | 2700K |
| 30 | 3000K |
| 40 | 4000K |

example of code composition 1004.00 4 R 40 E 30 WD

TECHNICAL FEATURES

| | |
|--------------------------|--|
| Code | 1004.00 XX |
| Type | Downlight 90° ▲ |
| Material | 00: Coral® |
| Weight | 0.8 Kg |
| Mounting | Ceiling recessed |
| IP rating | IP20 |
| Insulation class | III |
| Control gear | Constant current electronic driver (not included) |
| Cut out for plasterboard | Ø 85 mm |
| Lamp type | LED 500 mA ⚡ Vf: 18 VDC |
| Lamp wattage | 1 x 9W |
| Luminous efficacy | 1125 lm - 3000K |
| Light distribution | Wide beam 40° |
| Fitting | - |
| Light colour | White 3000K White 2700K 4000K (on request) |
| Light hole | Ø 50 mm |
| Voltage connection | By driver (optional) |
| CRI | 90 |
| Emergency | - |
| Energy efficiency class | A++ |
| Note | On request available dimmable PUSH or DALI. |

OPTIONAL ACCESSORIES

| product code | optional code | description | info |
|--------------|---------------|---|---|
| 1004.00 XX | H8500.E | Constant current electronic driver. Remote installation | Suitable for n°2 code 1004.00 XX - 500 mA |
| | H8500.B | Constant current electronic driver | Suitable for n°1 code 1004.00 XX - 500 mA |