

INVISILED




MINIME DIMENSIONI: 40 x 40 mm.


La luce scaturisce improvvisamente da un punto nella parete, pura e delicata si diffonde in modo omogeneo nello spazio, avvolgendo, indisturbata, tutto l'ambiente. Invisiled, incasso a scomparsa totale in AirCoral® per installazione in parete e soffitto di cartongesso o laterizio, è pensato per progetti in cui la luce deve essere protagonista. Invisiled si adatta ad ogni ambiente, regalando concretezza agli spunti del progettista, inserendosi con discrezione negli spazi.

MINIMUM DIMENSIONS: 40 x 40 mm.

Pure and delicate light suddenly springs from a spot on the wall, and it spreads out homogeneously in the space, enfolding the whole room, undisturbed. Invisiled, a totally disappearing recessed luminaire made of AirCoral®, installable on plasterboard or brick walls and ceilings, is studied for projects where light has the main role. Invisiled fits into any environment, giving concreteness to the designer's inspirations, and discreetly integrating itself into spaces.



TECHNICAL FEATURES

Code	6348.AC
Type	Downlight 90° Wall recessed 90° 
Material	AC: AirCoral®
Absorption capacity*	1,05 m²
Weight	0,3 Kg
Mounting	Wall and ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Constant current electronic driver (not included)
Cut out for plasterboard	90 x 90 mm
Lamp type	LED Vt: 3 VDC
Lamp wattage	1W - 350 mA 2W - 500 mA
Luminous efficacy	75 lm - 3000K 350 mA 170 lm - 3000K 500 mA
Light distribution	Narrow beam 14°
Fitting	-
Light colour	White 3000K White 2700K (on request)
Light hole	40 x 40 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation. This product could be ordered with IP44 / IP65 protection grade (see OUTDOOR section - code 6349.CW / 6347.CW).

OPTIONAL ACCESSORIES

product code	optional code	description	info
6348.AC	H8350	Constant current electronic driver	Suitable for n°1 code 6348.AC - 350 mA
	H8500.B	Constant current electronic driver. Remote installation	Suitable for n°5 code 6348.AC - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°2 code 6348.AC - 500 mA

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²

