

# GENIUSQUARE BRASS




RIFLESSI DORATI  
SENZA ALTERARE IL COLORE DELLA LUCE.

Geniusquare Brass è un apparecchio a scomparsa totale, con scocca realizzata in AirCoral®, ideale per installazioni a soffitto in interni, sia su cartongesso che laterizio. In questa variante, che conserva tutte le caratteristiche della linea Genius, l'arretramento del punto luce è corredato da un inserto in ottone che partecipa alla diffusione luminosa, generando una tonalità di luce più calda e sfumature variegata adatte a situazioni di "relaxed ambience". La parte elettrica è estraibile direttamente dal foro luce, grazie alla meccanica push-pull, che facilita l'estrazione e la sostituzione della sorgente LED. L'unica apertura visibile è il foro da 20 x 20 mm, senza la necessità di alcuna botola di ispezione e tantomeno di interventi invasivi in caso di manutenzione.

GOLDEN REFLEXES  
WITHOUT CHANGING THE COLOUR OF THE LIGHT.

Geniusquare Brass is a totally recessed luminaire, with body made in AirCoral®, ideal for indoor ceiling-mounted installations, both on drywall and bricks. In this version, which retains all the features of the Genius line, the backing on the light emission hole is fitted with a brass insert which helps to spread light, generating a warmer tone and variegated shades suitable for relaxed ambience situations. The electrical part can be removed through the light hole, thanks to a push-pull mechanism making it easy to pull the LED light source out and replace it. The only visible aperture is the 20 x 20 mm (0.79" x 0.79") outlet, with no need for any inspection hatch, nor for invasive maintenance operations.



## CODE COMPOSITION

<b>1895.AC</b> 4 R 40 E _WD	<i>light colour</i>	
	<b>27</b>	2700K
	<b>30</b>	3000K
	<b>40</b>	4000K
<b>1896.AC</b> 4 R 40 E _ND	<i>light colour</i>	
	<b>27</b>	2700K
	<b>30</b>	3000K
	<b>40</b>	4000K
<b>example of code composition</b>	1895.AC 4 R 40 E <b>30</b> WD	

## TECHNICAL FEATURES

Code	<b>1895.AC</b> XX	<b>1896.AC</b> XX
Type	Downlight 90°	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	1.39 m²	1.39 m²
Weight	0.8 Kg	0.8 Kg
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20
Insulation class	III	III
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic driver and inverter (included)
Cut out for plasterboard	135 x 110 mm	135 x 110 mm
Lamp type	LED 700 mA Vf: 11.5 VDC	LED 700 mA
Lamp wattage	1 x 8.5W	1 x 8.5W
Luminous efficacy	1000 lm - 3000K	1000 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)
Light hole	20 x 20 mm	20 x 20 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90
Emergency	-	<b>1 hour</b>
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
<b>1895.AC</b> XX	<b>H8700.E</b>	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1895.AC XX - 700 mA
	<b>BR1895LT</b>	Brick box	<b>Dimensions</b> L: 195 mm; W: 140 mm; D: 160 mm
<b>1896.AC</b> XX	<b>BR1896LT</b>	Brick box	<b>Dimensions</b> L: 195 mm; W: 140 mm; D: 160 mm

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²