

GENIUS BRASS



RIFLESSI DORATI
SENZA ALTERARE IL COLORE DELLA LUCE.



Genius Brass in AirCoral® è un incasso a scomparsa totale da interni per installazione in soffitto di cartongesso o laterizio. Il foro di emissione luce, di soli 20 mm e dotato di un cilindro in ottone, dona un tocco prezioso ad un prodotto già estremamente raffinato. Genius Brass è un prodotto che con le sue caratteristiche contribuisce ad aumentare il comfort visivo e generare una tonalità di luce più calda, rendendo gli ambienti più accoglienti.

La parte elettrica è estraibile direttamente dal foro luce con un semplice gesto della mano, grazie alla meccanica push-pull, che facilita l'eventuale estrazione e la sostituzione della sorgente LED in caso di manutenzione.

GOLDEN REFLEXES
WITHOUT CHANGING THE COLOUR OF THE LIGHT.

Genius Brass is a total recessed indoor luminaire made of AirCoral® and installable on plasterboards or brick ceilings. The light emission hole, only 20 mm wide, is provided with a brass cylinder which gives a precious touch to a product already extremely elegant. Genius Brass' characteristics enhance visual comfort and generates a warm light which makes the environments more welcoming.

The electrical part can be extracted directly from the emission hole with a simple hand gesture. This is possible thanks to the push-pull mechanism, which facilitates the eventual extraction and replacing of the LED source in case of maintaining.



TECHNICAL FEATURES

Code	1861.AC	1862.AC
Type	Downlight 90° 	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	1.39 m²	1.39 m²
Weight	0.8 Kg	0.8 Kg
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20
Insulation class	III	III
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic driver and inverter
Cut out for plasterboard	135 x 110 mm	135 x 110 mm
Lamp type	LED 700 mA ⚡ V _f : 11.5 VDC	LED 700 mA ⚡
Lamp wattage	1 x 8.5W	1 x 8.5W
Luminous efficacy	1000 lm - 3000K	1000 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)
Light hole	Ø 20 mm	Ø 20 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90
Emergency	-	1 hour
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1861.AC	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1861.AC - 700 mA
	BR1861LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)
1862.AC	BR1862LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



Il foyer, Piazza Teatro alla Scala - Michael Vincent Uy MVOU - Milan