



Z1 48V



CODE COMPOSITION

T048 L 00003		0	
<i>dimmiability</i>			
ND	non dimmable		
DA	DALI		
11	1-10V		
<i>light colour</i>			
27	2700K		
30	3000K		
40	4000K		
<i>lens</i>			
22	22°		
50	50°		
<i>finishing</i>			
W1	white		
B1	black		

example of code composition T048 L 00003 **W1 22 27 ND 0**

TECHNICAL FEATURES

Code	T048 L 00003 XX
Type	Projector ± 360° / ± 90°
Material	Aluminum
Finishing	White Black
Weight	0.4 Kg
Mounting	Track 48V
IP rating	IP40
Insulation class	III
Control gear	Electronic driver on board (included)
Lamp type	LED
Lamp wattage	1 x 6W
Luminous efficacy	520 lm - 3000K
Light distribution	Beam 22° Beam 50° (on request)
Light colour	White 3000K White 2700K White 4000K (on request)
Voltage connection	48 VDC
CRI	>90
Note	-

Z1 48V è un apparecchio per binari a 48V caratterizzato da un proiettore miniaturizzato di soli 23 mm di diametro, completamente direzionabile sugli assi verticale ed orizzontale. Disponibile con finitura di serie bianca o nera, Z1 48V è un prodotto che garantisce alte prestazioni con il minimo impatto visivo.

Il proiettore Z1 48V ha sorgente luminosa a LED (COB) CRI >90, 3000K o 2700K (4000K su richiesta) alimentata in corrente continua con convertitore a scomparsa collocato all'interno dell'adattatore a binario.

Z1 48V is a 48V track fitting characterised by a miniaturised projector with a diameter of only 23 mm, completely directional on vertical and horizontal axes. Available in a standard white or black finish, Z1 48V is a product which guarantees high performances with a minimum visual impact.

The Z1 48V projector has an LED (COB) CRI >90, 3000K or 2700K light source (4000K on request) fed in direct current with incorporated convertor located inside the track adaptor.

