Murané

24V DC M11505.010.0410

champagne




Data sheet

CODE	M11505.010.0410
SYSTEM POWER CONSUMPTION	2,7W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	120lm
WEIGHT	0,53 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm



Technical drawing





Turned brass wiring support. Diffuser in blown glass with bronze colour.

Turned aluminium closing disk in champagne polyacrylic paint.

5m (196,9") long suspension and power cable in transparent PVC. Provided without power canopy, complete with cable clamp on the cable's free extremity.

Polar diagram

Murané

Accessories / power supply

хм100/24 DIM С Є ЕНЦ 🗵 🐵	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
хм18/24 DIM С € ЕПЕ 🗵 🐨	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	175 mm 6 Yu- 10 1 175 mm 6 Yu-
XM35/24 DIM C € EAL 🗵 💿	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	6 %**
хм6-20 UNI С Є ЕНГ. 🗵 💿	LED driver, 4÷20W 250÷700mA.	S2 mm 22 mm 22 mm
хм60/24 DIM С Є ЕПП 🗵 🐨	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	118 mm 4 ²/₂* gg ≥ gg ≥ gg ≥ gg ≥ gg ≥ gg ≥ gg ≥ gg
YDV.024.030.A01 Ce [fii] 🗵 🐨	LED driver, 30W 24V DC.	and the second s
YDV.024.060.A01	LED driver, 60W 24V DC.	101 mm 101 mm 7.74/
YDV.024.120.A01	LED driver, 120W 24V DC.	Віст В

Murané

Accessories / power supply and fixing

XM8901-03 LED	Canopy for power supply and suspension up to 3 24V DC constant voltage models maximum.	1.3.5 1.3,6
CEERE 🗵 🐵		<u>با</u> بری الح 42
		<u>42</u> 16 ⁵ /9″
XM8901-05 LED	Canopy for power supply and suspension up to 5 24V DC constant voltage models maximum.	ୁ ଅନ୍ତି : ଅନ୍ତି
CE EHL 🗵 🖤		· · · · · · · · · · · · · · · · · · ·
XM8901-06 LED	Canopy for power supply and suspension up to 6 24V DC constant voltage models maximum.	
CE ERI 🗵 🖤		25.2
		42 16 %9*
XM8901-09	Canopy for power supply with 9 outputs.	
CE ERI 🗵 🖤		-% 21 57
		72,5 28 4/r
XM8901-15	Canopy for power supply with 15 outputs.	
CE ERE 🗵 🐵		 17 %*
		72.5
		28 4/r*
XM9001-03	Canopy for power supply with 3 outputs.	0.5 0.1 1/2
CE [fill 🗕 🐵		
	Canopy for power supply with 7 outputs.	
XM9001-07	Canopy for power supply with 7 outputs.	3.9
CEHH		
XM9001-12	Canopy for power supply with 12 outputs.	
CEERE 🗵 🐵		23 4H
XM9001-21	Canopy for power supply with 21 outputs.	8: ×
CEEN 🗵		

Murané

Accessories / power supply and fixing

XM9201-01



Recessed canopy for electric cable suspensions. Suitable for 24V fixtures: remote driver 24V needed.

