


BEAN

Steplights

design Roberto Mantovani



The Bean range offers IP67 asymmetrical emission devices of extremely compact dimensions, for ground or wall installation.

La gamma Bean propone apparecchi ad emissione asimmetrica IP67 di dimensioni estremamente ridotte, per installazione a terra o a parete.

La gamme Bean propose des appareils à émission asymétrique IP67 de dimensions extrêmement réduites, pour installation au sol ou au mur.

Die Bean-Serie bietet extrem kleine IP67-Asymmetrieleuchten für die Boden- oder Wandmontage.

La gama Bean propone aparatos de emisión asimétrica IP67 de dimensiones extremadamente pequeñas, para instalación en el suelo o en la pared.



IP67 made in Italy

Supply current

350mA (V_i 2,9V)

Power


1W

Series wiring

Dimensions



Photometric diagrams



CCT/CRI/Flux


CCT	Flux
2700K	101lm
3000K	109lm
4200K	116lm
6000K	132lm

Code construction

EA1	X	X					
B	G	N	K	Z			
White	Grey	Black	COR-TEN	INOX AISI 316L			
0	1	2	3	6	7	8	
2700K	3000K	4200K	6000K	Blue	Green	Red	

Optionals

CSLN01
Recessing box



Drivers

350 mA	on/off	dimmable
AL1034 (1..11)	30mm IP20	AL4000 (1..12)
AL1035 (1..11)	40mm IP20	AL4051 (1..12)
AL1037 (1..16)	55mm IP20 S.P.	AL4053 (1..12)
AL9011 (1..12)	60mm IP67	