PANZERI

Three

220-240V AC ON-OFF

P03901.011.0406





Data sheet

CODE	P03901.011.0406
SYSTEM POWER CONSUMPTION	10W
EFFICACY	59.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	850lm
LUMEN OUTPUT	595lm
EFFICIENCY	70%
WEIGHT	0,51 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.

Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

 $\label{prop:extruded} \textbf{Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint.}$

Aluminium dissipation plate. Flat frosted glass diffuser.


Pickled sheet metal frame in polyacrylic paint.








Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

PANZERI

Three

Accessories / dimming

XM14/230

Dimmable device for 230V LED modules, 5÷100W.



