# PANZERI

#### Арр

220-240V AC ON-OFF A09801.002.0406

#### Data sheet

CODE	A09801.002.0406
SYSTEM POWER CONSUMPTION	36W
EFFICACY	79.5lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2862lm
LUMEN OUTPUT	2862lm
EFFICIENCY	100%
WEIGHT	2,03 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	27,0 x 36,0 x 14,0 cm




INDIRECT LIGHT

Wall lighting fixture for interiors, with indirect light emission. Die-cast aluminium wall bracket in polyacrylic paint. Extruded aluminium structure in white, mat brass or titanium polyacrylic paint.


# CE ERE

### Technical drawing



#### Polar diagram

white



## PANZERI

## Арр

Accessories / dimming

XM14/230

Dimmable device for 230V LED modules, 5÷100W.





3,2 1 ¼″

1,8 5/7"