


## XJR8



## CODE COMPOSITION

1031 WH 2 R 40 E \_ WD

light colour

27	2700K
30	3000K
40	4000K

1034 WH 4 R 40 E 98 WD

example of code composition 1031 WH 2 R 40 E 30 WD

## TECHNICAL FEATURES

Code	1031 XX	1034 XX
Type	Tiltable downlight and wall recessed $\pm 30^\circ$ 	Tiltable downlight and wall recessed $\pm 30^\circ$ 
Material	Aluminum	Aluminum
Finishing	White	White
Weight	0.25 Kg	0.25 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP20	IP20
Insulation class	III	III
Control gear	Constant current electronic driver (not included)	Remote constant current electronic driver** (not included)
Cut out for plasterboard	76 x 76 mm	76 x 76 mm
Lamp type	LED 500 mA Vf: 18 VDC	LED 350 mA Vf: 17 VDC
Lamp wattage	1 x 9W	1 x 6W
Luminous efficacy	1125 lm - 3000K	600 lm (from 1800K up to 3000K)
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K   4000K (on request)	Dimming range 1800/3000K
Voltage connection	By driver (optional)	By driver (optional)
CRI	>90	95
Emergency	-	-
Note	On request available dimmable PUSH or DALI.	On request available dimmable PUSH or DALI, remote installation.

\*\*XJR8 Dim to Warm requires dimming: amplitude (AM) IEEE1789-2015 dim to warm wide range input voltage.




matt white

XJR8 sa rispondere con tecnicità alle richieste di ogni singolo ambiente: apparecchio da interni a incasso per installazione in parete e soffitto di cartongesso disponibile con finitura bianca. La sorgente luminosa, retrocessa e con meccanica a vista orientabile, dona una luce precisa e puntuale senza sacrificare l'eleganza degli spazi.

XJR8, a recessed indoor luminaire installable on plasterboard walls or ceilings, provides technical quality for any types of environment. Available with white finishings, it has a backward light source with visible mechanisms which emanates precise and punctual beams without renouncing space elegance.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
1031 XX	H8500.E	Constant current electronic driver	Suitable for n°2 code 1031 XX - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 1031 XX - 500 mA
1034 XX	H8350DA.AM	Dimming: amplitude (AM) DALI	Suitable for n°2 code 1034 XX
	H8350PH.AM	Dimming: amplitude (AM) PUSH	Suitable for n°2 code 1034 XX



CODE COMPOSITION

1032 WH 6 R 00 E 00 WD

1033 WH 6 R 00 E 00 WD

TECHNICAL FEATURES

Code	1032 XX	1033 XX
Type	Tilttable downlight and wall recessed +/-30° 	Tilttable downlight and wall recessed +/-30° 
Material	Aluminum	Aluminum
Finishing	White	White
Weight	0.15 Kg	0.15 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP20	IP20
Insulation class	III	I
Control gear	Electronic transformer (not included)	-
Cut out for plasterboard	76 x 76 mm	76 x 76 mm
Lamp type	QR CB 51 	QPAR 16 
Lamp wattage	50W max	50W max
Luminous efficacy	-	-
Light distribution	-	-
Fitting	GU5.3	GU10
Light colour	-	-
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	-	-
Emergency	-	-
Note	-	-

OPTIONAL ACCESSORIES

product code	optional code	description	info
1032 XX	H8060.LED	Dimmable electronic transformer	<b>Max watt 60W Volts · Hz 230/12V · 50/60Hz</b>
	0008KIT	Kit LED dimmable	<b>Bulb 7W · 12V</b>
1033 XX	0009KIT	Kit LED dimmable	<b>Bulb 6W · 220-240V</b>

