Emma

220-240V AC M09151.000.0200

Data sheet

CODE	M09151.000.0200
SYSTEM POWER CONSUMPTION	max 57W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	* included
COMPATIBLE SOURCES	LED retrofit bulb 8W E27 2700K Ra80 1050lm (no dimming) * / max 57W E27
COLOUR TEMPERATURE	2700K Ra>80
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX	1050lm
WEIGHT	1,47 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <6
PACKING DIMENSIONS	0,0 × 0,0 × 0,0 cm

CEERE



black/white diffuser






Multiple suspension lighting fixture for interiors, with direct and indirect light emission. Rough aluminium structure.

Diffuser in blown glass with white, crystal, steel, amber, bronze, tobacco or green ribbing finish.

Turned pickled sheet metal closing disk in black or mat brass polyacrylic paint. 3,5m (137,8") long suspension and power cable in PVC with black fabric covering. Provided without power canopy, complete with polycarbonate hook.

Technical drawing



Emma

Accessories / power supply

M7901/1	Canopy for power supply.	
C E E E E E E E E E E E E E E E E E E E		a 10,6 4 ^{1/6}
M7901/2	Canopy for power supply with 2 outputs.	
C € EAL 🗶 📾		0 0,0 10,6 */6*
M7901/3	Canopy for power supply with 3 outputs.	
C E EHI 🗵 📾		a 10.6 b 10.6
M7902/1	Canopy for power supply.	
C E EAL 🖄 📾		a 10,6 4 1/6°
M7902/2	Canopy for power supply with 2 outputs.	
C € EAL 🗶 📾		a 10,6 a
M7902/3	Canopy for power supply with 3 outputs.	
C € EAL 🗶 📾		a a b b b c c c c c c c c c c
M91/94/9702	Canopy for power supply up to 9 M091000.0200/M094000.0200/M097000.0200 models maximum.	4 ¹
C E EHI 🗵 🙉		21 8 2/r*

Emma

Accessories / power supply and fixing

XM8901-03	Canopy for power supply with 3 outputs.	
CE III 🗵 🐵		3** 3
	Canopy for power supply with 5 outputs.	6. ⁸⁶
XM8901-05	Canopy for power supply with 5 outputs.	
CE [III] 🖄 🐵		
XM8901-06	Canopy for power supply with 6 outputs.	
CE ERI X @		
		42 16 %/3″
XM8901-09	Canopy for power supply with 9 outputs.	
CE ERE 🗵 🐵		45 17 %*
		72.5 28 4/7
XM8901-15	Canopy for power supply with 15 outputs.	
CE EAE 🕱 🐵		
		72.5 28 \/r
XM9001-03	Canopy for power supply with 3 outputs.	٥; الم
CE III 🗵 🐵		·
XM9001-07	Canopy for power supply with 7 outputs.	
CE EAE 🗵 🙉		
		39.5 15 4/7
XM9001-12	Canopy for power supply with 12 outputs.	۵٫۲
CE EAL 🗵 🐵		Q 21
XM9001-21	Canopy for power supply with 21 outputs.	
CE III 🗵 🐵		· · · · · · · · · · · · · · · · · · ·
		<u> </u>

Emma

Accessories / power supply and fixing

XM9201-01



Recessed canopy for electric cable suspensions. Suitable for 24V fixtures: remote driver 24V needed.



Emma

Accessories / fixing

M75D	Suspension and adjustment device for electric cable.	4.2 1 ² /3"
		1.2°9
M800 CEERI 🖉 💿	Polycarbonate hook for suspension.	3.2 1 _{/4} "
		() () () () () () () () () ()