PANZERI

Zero Square

24V DC M03219.075.0510

Data sheet

CODE	M03219.075.0510
SYSTEM POWER CONSUMPTION	36W
EFFICACY	84.97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	4252lm
LUMEN OUTPUT	3059lm
EFFICIENCY	71.9%
WEIGHT	1,21 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	83,0 x 83,0 x 10,0 cm

mat brass






Single or multiple suspension lighting fixture for interiors, with direct and indirect light emission.

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables. 5m (196,9") long power cable in transparent PVC. Provided without power canopy.



Technical drawing



Polar diagram



PANZERI

Zero Square

Accessories / power supply

Canopy for power supply of 1 Zero Shapes model, with DALI/Push DIM driver.	1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1
	•
	20.6 8 ½
Canopy for power supply of 2 Zero Shapes models, with DALI/Push DIM drivers.	88 71 11
	225 12 %
Construction of a Zero Change models with DALL/Dush DIM drivers	12 44* 28 12:
Canopy for power supply of 3 Zero Snapes models, with DALI/Push DIM drivers.	
	225 12%*
	12.4/x*
Canopy for power supply of 4 Zero Shapes models, with DALI/Push DIM drivers.	38
	225
	Canopy for power supply of 2 Zero Shapes models, with DALI/Push DIM drivers.

PANZERI

Zero Square

Accessories / power supply and fixing

XM03319.531.0002	Canopy for power supply and suspension of 1 Zero Shapes Horizontal model, with DALI/Push DIM driver.	14 96
CE FHI X		20,8 8 %
XM03319.532.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	
CE ERL X		22 5 10 %*
XM03319.533.0002	Canopy for power supply and suspension of 3 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	
CE EHL X		22.5 10.7%*
XM03319.534.0002	Canopy for power supply and suspension of 4 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	80 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
CE ERL X		20.5 12.5%
XM03419.552.0002	Canopy for power supply and suspension of 1 Zero Shapes Horizontal and 1 Zero Round Vertical models, with DALI/Push DIM drivers.	
CE ERL X		28.5 15 Y/
XM03419.553.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal and 1 Zero Round Vertical models, with DALI/Push DIM drivers.	
C C EHL X III		285 15 Y/
XM03419.554.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal and 2 Zero Round Vertical models, with DALI/Push DIM drivers.	811 ···································
CE FHI X		385