# **PANZERI**

## Gonio

220-240V AC dimmable (DALI/Push DIM)

A01902.030.0502





#### Data sheet

CODE	A01902.030.0502
SYSTEM POWER CONSUMPTION	26W
EFFICACY	83.38lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3120lm
LUMEN OUTPUT	2168lm
EFFICIENCY	69.5%
WEIGHT	1,08 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 35,0 x 10,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal wall bracket in polyacrylic paint.

 ${\sf Extruded\ aluminium\ structure\ in\ white,\ black,\ bronze,\ mat\ brass\ or\ titanium\ polyacrylic}$ 

Extruded acrylic diffusers with opaline finish.


Die-cast aluminium end caps in polyacrylic paint.







### **Technical drawing**



## Polar diagram

