PANZERI

Willy Glass

220-240V AC dimmable (DALI/Push DIM)

L07633.060.0402

metallized grey



Data sheet

CODE	L07633.060.0402
SYSTEM POWER CONSUMPTION	40W
EFFICACY	89.68lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4592lm
LUMEN OUTPUT	3587lm
EFFICIENCY	78.1%
WEIGHT	8,38 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	69,0 x 69,0 x 53,0 cm



Suspension lighting fixture for interiors, with direct and indirect light emission.

Turned pickled sheet metal structure in metallized grey polyacrylic paint.

Extruded aluminium heat sink.

Lampshade in mat white blown glass.

Diffuser in modelled frosted glass. 2m (78,7") long steel suspension cables.

2,2m (86,6") long power cable in transparent PVC.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in metallized grey polyacrylic paint.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270