

JACOBBOX




INCASSO DIREZIONABILE.

Jacobbox è un apparecchio da interni a scomparsa totale per installazione in parete e soffitto di cartongesso o laterizio realizzato in AirCoral®. La sorgente luminosa retrocessa con meccanica a vista orientabile dona una luce precisa e puntuale, senza sacrificare l'eleganza degli spazi.

ADJUSTABLE RECESSED FITTING.

Jacobbox is a totally disappearing indoor recessed luminaire, installable on plasterboard or brick walls and ceilings made of AirCoral®. With its visible and adjustable mechanic structure, the recessed luminescent source emanates a precise and punctual light without renouncing space elegance.



TECHNICAL FEATURES

Code	6248.Z.AC	6249.Z.AC	6241.AC	6244.AC
Type	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	3.07 m²	3.07 m²	3.07 m²	3.07 m²
Weight	1.3 Kg	1.8 Kg	1.1 Kg	1.1 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP20	IP20	IP20	IP20
Insulation class	III	III	III	I
Control gear	Constant current electronic driver (not included)	Constant current electronic driver	Electronic transformer (not included)	-
Dimensions	A: 130 mm	A: 130 mm	A: 130 mm	A: 130 mm
Cut out for plasterboard	160 x 160 mm	160 x 160 mm	160 x 160 mm	160 x 160 mm
Lamp type	LED 500 mA ⚡ V: 18 VDC	LED 500 mA ⚡ V: 18 VDC	QR CB 51 ⚡	QPAR 16 ⚡
Lamp wattage	1 x 9W	1 x 9W	1 x 50W max	1 x 50W max
Luminous efficacy	1125 lm - 3000K	1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	Wide beam 40°	-	-
Fitting	-	-	GU5.3	GU10
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)	-	-
Light hole	90 x 90 mm	90 x 90 mm	90 x 90 mm	90 x 90 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90	-	-
Emergency	-	1 hour	-	-
Energy efficiency class	A++	A++	A	A
Note	On request available dimmable PUSH or DALI.	-	-	-

OPTIONAL ACCESSORIES

product code	optional code	description	info
6248.Z.AC	H8500.E	Constant current electronic driver	Suitable for n°2 code 6248.Z.AC - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 6248.Z.AC - 500 mA
	BR6248LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6241.AC	H8060.LED	Dimmable electronic transformer	Max watt 60W Volts · Hz 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	Bulb 7W · 12V
	BR6241LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6244.AC	0009KIT	Kit LED dimmable	Bulb 6W · 220-240V
	BR6244LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



Private house - ASZ Architeti

Private villa - Forli