



ELIOS



INCASSO CON VETRO RETROCESSO,
MASSIMA INVISIBILITÀ.

Un nome evocativo, un design circolare che si integra con l'ambiente in cui viene installato, avvolgendo gli ambienti di luce viva. Elios è un apparecchio illuminante da interni, un incasso a scomparsa totale realizzato in AirCoral® per installazione a soffitto di cartongesso o laterizio. L'armonia delle forme è espressione di assoluta eleganza, la qualità dei materiali è garanzia di durata nel tempo e resistenza, per una luce pura e dallo stile unico.
Elios: luce che illumina e che purifica, esaltando in modo naturale ogni ambiente.

RECESSED FITTING WITH REAR GLASS,
MAXIMUM INVISIBILITY.

An evocative name, a circular design that fits in the space it is installed in, enveloping rooms in bright light. Elios is a totally disappearing indoor recessed luminaire made of AirCoral®, installable on plasterboard or brick ceilings. Its purity of shapes is an expression of absolute elegance, the quality of its materials guarantees long duration and resistance, for a pure light and a unique style.
Elios: a light that illuminates and purifies, naturally exalting every space.

TECHNICAL FEATURES

Code	6371.AC (fig. A)	6376.AC (fig. B)	6385.AC (fig. B)	6381.AC (fig. B)	6383.AC (fig. B)
Type	Tiltable downlight ± 30° 	Downlight 90° 	Downlight 90° 	Downlight 90° 	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	5.28 m²	5.28 m²	5.28 m²	5.28 m²	5.28 m²
Weight	3.6 Kg	3.6 Kg	3.8 Kg	2.6 Kg	2.6 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40	IP40	IP40
Insulation class	III	I	I	I	I
Control gear	Dimmable electronic transformer	Electronic ballast	Electronic ballast	Constant current electronic driver	Dimmable constant current driver
Cut out for plasterboard	Ø 270 mm	Ø 270 mm	Ø 270 mm	Ø 270 mm	Ø 270 mm
Lamp type	QR 111 	TC-TEL 	TC-TEL 	LED 1050 mA 	LED 350 mA
Lamp wattage	1 x 100W max	2 x 26/32W	2 x 26W	1 x 40W	2 x 6.5W
Luminous efficacy	-	-	-	4680 lm - 3000K	2 x 810 lm - 3000K
Light distribution	-	-	-	Wide beam 40°	Wide beam 120°
Fitting	G53	Gx24q-3	Gx24q-3	-	-
Light colour	-	-	-	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)
Light hole	Ø 200 mm	Ø 200 mm	Ø 200 mm	Ø 200 mm	Ø 200 mm
Voltage connection	220-240V / 12V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	-	-	-	>90	>90
Emergency	-	-	1 hour	-	-
Energy efficiency class	A	A	A	A++	A+
Note	Extra white satin glass with transparent central part Ø 110 mm. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling. Trailing-edge and leading-edge dimming (20 - 100%).

OPTIONAL ACCESSORIES

product code	optional code	description	info
6371.AC	00010KIT	Kit LED dimmable	Bulb 10W · 12V
6376.AC	BR6376LT	Brick box	Dimensions L: 445 mm; W: 270 mm; D: 225 mm (instructions on page 502)
6383.AC	BR6383LT	Brick box	Dimensions L: 445 mm; W: 270 mm; D: 225 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2,7 m in height and therefore expressed in m²



Madiolanum headquarter - Milan