Technical features






402802

FRAME MEDIUM SQUARE Designed by NAVA + AROSIO

Square 200x200mm surface mounted luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, acid-etched tempered glass diffuser white painted internally, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 36 x mid-power SAMSUNG 2835 LED. IP65 rating.



200 mm

17	-	-	-	-	٦	
					I	
					I	
1	-	-	-	-	68	

light source	light l optio		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		diffused	808	50.50
4000°K neutral-white				
high-power led		diffused	844	52.75

Finish color options:

Textured Grey RAL 9006



Matt Black (on request)

Technical data

	-
Wattage	16 WATT
IP Rating	IP65
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	36 x mid-power SAMSUNG 2835 LED
Screws	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Acid-etched tempered glass diffuser white painted internally
Power cable	0,3 mt. power cable included
Gross weight	3,50 Kg



