# PANZERI

### Zero Round

24V DC M03302.050.0410

#### Data sheet

CODE	M03302.050.0410
SYSTEM POWER CONSUMPTION	25W
EFFICACY	81.56lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	2835lm
LUMEN OUTPUT	2039lm
EFFICIENCY	71.9%
WEIGHT	0,83 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	58,0 x 58,0 x 10,0 cm








Single or multiple suspension lighting fixture for interiors, with direct and indirect light emission.

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables. 5m (196,9") long power cable in transparent PVC. Provided without power canopy.



### Technical drawing



#### Polar diagram



#### Panzeri.it - 05/09/2022 - Zero Round - M03302.050.0410

# PANZERI

## Zero Round

### Accessories / power supply

XM03302.511.0002	Canopy for power supply of 1 Zero Shapes model, with DALI/Push DIM driver.	
CE HI 🗵 🐵		•••
		20.6 8 ½*
XM03302.522.0002	Canopy for power supply of 2 Zero Shapes models, with DALI/Push DIM drivers.	3.6
CE EAL 🖄 🐵		22.5
		12.4%*
XM03302.523.0002	Canopy for power supply of 3 Zero Shapes models, with DALI/Push DIM drivers.	8) <u>*</u>
CEER		$\cdot$
		<u>32,5</u> 12.4/x*
XM03302.524.0002	Canopy for power supply of 4 Zero Shapes models, with DALI/Push DIM drivers.	88 197
CE EAL 🖄 🐵		22.5
		12 4/4*

## PANZERI

## Zero Round

### Accessories / power supply and fixing

XM03302.531.0002	Canopy for power supply and suspension of 1 Zero Shapes Horizontal model, with DALI/Push DIM driver.	[4] [8]
CE HIL 🗵 🐵		20.6 8 V5
XM03302.532.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	gg XI
CE EAL 🕱 🐵		22.5 12.54
XM03302.533.0002	Canopy for power supply and suspension of 3 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	
CE EHL 🗵 🐵		22 <u>5</u> U 5%
XM03302.534.0002	Canopy for power supply and suspension of 4 Zero Shapes Horizontal models, with DALI/Push DIM drivers.	98 Jan 199
CE EHL 🗵 🐵		22.5 12 W.
XM03402.552.0002	Canopy for power supply and suspension of 1 Zero Shapes Horizontal and 1 Zero Round Vertical models, with DALI/Push DIM drivers.	81ž
CE EHL X		38.5 15 vr
XM03402.553.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal and 1 Zero Round Vertical models, with DALI/Push DIM drivers.	96 20 20
CE ERL 🗵 🐵		305 10 V/
XM03402.554.0002	Canopy for power supply and suspension of 2 Zero Shapes Horizontal and 2 Zero Round Vertical models, with DALI/Push DIM drivers.	91ž
CE HIL 🗵 🐵		