
### Brooklyn Round

220-240V AC dimmable (DALI/Push DIM) L23201.360.0402




Suspension lighting fixture for interiors, with direct light emission. Bended extruded aluminium structure in white, black or mat brass polyacrylic paint. Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables. 5m (196,9") long power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and covering in white polyacrylic paint.


#### Data sheet

Data sheet		
CODE	L23201.360.0402	
SYSTEM POWER CONSUMPTION	109W	
EFFICACY	54.41lm/W	
LIGHT SOURCE	LED	
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h	
COLOUR TEMPERATURE	3000K Ra>90	
LIGHT DISTRIBUTION	diffused	
POWER SUPPLY	220-240V AC	
FREQUENCY	50/60Hz	
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)	
DRIVER	integrated included	
NOMINAL LUMINOUS FLUX	13680lm	
LUMEN OUTPUT	5931lm	
EFFICIENCY	43.4%	
WEIGHT	5,78 Kg	
PROTECTION DEGREE	IP40	
COLOUR TOLLERANCES	SDCM 3	
GLOW WIRE TEST PERFORMANCE	850°	
PACKING DIMENSIONS	200,0 x 200,0 x 11,0 cm	




### Technical drawing





#### Polar diagram

white



## Brooklyn Round

#### Accessories / power supply

XM150/24 DIM

LED driver, 150W 24V DC, DALI/Push DIM dimmable.



.N.1 844 902		
101		
	225 mm	

## Brooklyn Round

#### Accessories / power supply and fixing

XM23101.538.0099

CE ERE 🗵

Canopy for power supply with 8 outputs and to join 7 steel cables, for up to 8 Brooklyn Round models maximum.





## Brooklyn Round

Accessories / fixing

XM231/23201L

Plate for multiple suspensions.





