

Technical features














808001 - 808003


O MEDIUM POLE

Designed by NAVA + AROSIO

Pole-mounted projector for outdoor installation on a pole; with U shape fixing bracket allowing vertical adjustment of $+90^{\circ}$ / -40° . Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets, with screws in stainless steel. Built-in LED driver. IP66 rating.


808001








808003








Technical data

IP Rating	IP66
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	Not included



808001	QUBO MEDIUM COB POLE - 16 WATT 220-240V 50-60HZ		
light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-whi	ite		
cob led	14°	1.900	118.75
cob led	35°	1.813	113.31
cob led	55°	1.722	107.62
4000°K neutral-white			
cob led	14°	2.000	125.00
cob led	35°	1.900	118.75
cob led	55°	1.805	112.81

Technical data		
Wattage	16 WATT	
Light source	1 x COB CREE "CXB 1512" LED	
Gross weight	3,50 Kg	

Colors options

Textured Grey RAL 9006 Anthracite Grey RAL 7016 Matt Black (on request)

808003	QUBO MEDIUM HP POLE - 20 WATT 220-240V 50-60HZ			
light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
3000°K warm-white				
high-power led	4°	2.050	102.50	
high-power led	10°	2.000	100.00	
high-power led	28°	1.950	97.50	
4000°K neutral-white				
high-power led	4°	2.100	105.00	
high-power led	10°	2.050	102.50	
high-power led	28°	2.000	100.00	

Technical data		
20 WATT		
3 x CREE "XHP35" LED		
3,50 Kg		

Colors options

Textured Grey RAL 9006 Anthracite Grey RAL 7016 Matt Black (on request)

POLES & ACCESSORIES

Full technical details of poles and accessories for poles are available at the end of the catalogue

BURIED POLES		
code	h. mm.	
809901	3.500	
809902	4.500	
809903	5.500	
809909	TOP CAP DIAM 76mm.	

