PANZERI

Jackie

220-240V AC dimmable (Step DIM)

A07702.000.0409





Data sheet

| CODE | A07702.000.0409 |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 10W |
| EFFICACY | 70.6lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L90 (B10) 50.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | adjustable |
| BEAM ANGLE | 90° |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (Step DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 884lm |
| LUMEN OUTPUT | 706lm |
| EFFICIENCY | 79.9% |
| WEIGHT | 0,47 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 12,0 x 24,0 x 13,0 cm |
| | |




Wall lighting fixture for interiors, with swivelling light beam. Pickled sheet metal wall bracket in polyacrylic paint. Die-cast aluminium wall plate in polyacrylic paint. $\label{thm:continuous} \mbox{Die-cast aluminium structure in white, black, red or titanium polyacrylic paint.}$ Die-cast aluminium head rotating on two axes in polyacrylic paint. Modelled acrylic diffuser with mat finish and double serigraphy. Push-button to adjust luminosity according to 5 levels of visual comfort.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270