PANZERI

Planet Ring

220-240V AC emergency

L08301.070.0407

white



Data sheet

Data sileet	
CODE	L08301.070.0407
SYSTEM POWER CONSUMPTION	71W
EFFICACY	82.59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	emergency
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	8857lm
LUMEN OUTPUT	5864lm
EFFICIENCY	66.2%
DURATION IN EMERGENCY MODE	1h
WEIGHT	9,83 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	68,0 x 68,0 x 16,0 cm



Suspension lighting fixture for interiors, with direct light emission.

Pickled sheet metal structure in white polyacrylic paint.

Aluminium dissipation plate.

Pickled sheet metal closing frame in polyacrylic paint.

Diffuser in modelled polycarbonate with opaline finish.

Suspension kit with griplocks and 2m (78,7") long steel cables.

2,5m (98,4") long power cable in transparent PVC.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white polyacrylic paint.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270