### Clio

#### 220-240V AC

M09453.000.0200





#### Data sheet

CODE	M09453.000.0200
SYSTEM POWER CONSUMPTION	max 57W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	* included
COMPATIBLE SOURCES	LED retrofit bulb 8W E27 2700K Ra80 1050lm (no dimming) * / max 57W E27
COLOUR TEMPERATURE	2700K Ra>80
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX	1050lm
WEIGHT	1,29 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <6
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm












Multiple suspension lighting fixture for interiors, with direct and indirect light emission.  $Structure\ in\ pressed\ rough\ aluminium\ and\ pickled\ sheet\ metal\ in\ polyacrylic\ paint.$  $\hbox{Diffuser in blown glass with white, crystal, steel, amber, bronze, to bacco or green } \\$ ribbing finish.

Pickled sheet metal closing disk in black or mat brass polyacrylic paint.  $3.5 \mathrm{m}$  (137,8") long suspension and power cable in PVC with black fabric covering.  $\label{provided} \mbox{Provided without power canopy, complete with polycarbonate hook.}$ 

#### Technical drawing



## Clio

### Accessories / power supply

M7901/1	Canopy for power supply.		2,4
CE EHI 🗵 🙉		•	10,6 4 1/6"
M7901/2	Canopy for power supply with 2 outputs.		4,1 <u>+</u>
CE EHI 🗵 🙉		<b>a</b>	10,6
M7901/3	Canopy for power supply with 3 outputs.		2,4
CE EHI X		0 0	10,6
M7902/1	Canopy for power supply.		4.7
CE EHI X		•	10,6
M7902/2	Canopy for power supply with 2 outputs.		2,4
CE EHI X		(n)	4 1/6"
M7902/3	Canopy for power supply with 3 outputs.		4,1
CE EHI X		( o o o	10,6
M91/94/9702	Canopy for power supply up to 9 M091000.0200/M094000.0200/M097000.0200 models maximum.	4	14/-
CE EM 🗵 🙉		•	

## Clio

### Accessories / power supply and fixing

XM8901-03	Canopy for power supply with 3 outputs.	3.5
		3,5
		42 16 <sup>5</sup> /9"
XM8901-05	Canopy for power supply with 5 outputs.	3,55
CE HI 🗵 🙉		76
		30*
XM8901-06	Canopy for power supply with 6 outputs.	3.55
	Canapy to perior cappy that compates	
		25.2
		42 16 %"
XM8901-09	Canopy for power supply with 9 outputs.	& Q   = = = = = = = = = = = = = = = = = =
CE [HI 🗵 🙉		45
		72.5 28 4/*
XM8901-15	Canopy for power supply with 15 outputs.	3.8
CE FAIL X @		45
		72,5 28 4/r*
XM9001-03	Canopy for power supply with 3 outputs.	3.9
CE FHI 🗵 🙉		·
		39.5
XM9001-07	Canopy for power supply with 7 outputs.	3. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.
CE EHL X @		
		39,5
XM9001-12	Canopy for power supply with 12 outputs.	Q) - 200
CE III 🗵 👨		
		70 70 747 75
XM9001-21	Canopy for power supply with 21 outputs.	
CE [HI 🗵 🙉		
		OI 01

## Clio

### Accessories / power supply and fixing

XM9201-01

CE EHI 🗵 🙉

Recessed canopy for electric cable suspensions. Suitable for 24V fixtures: remote driver 24V needed.



## Clio

### Accessories / fixing

