




# ML



Un punto di vista puntuale, in grado di enfatizzare particolari e spazi esclusivi: ML, apparecchio illuminante da interni per installazione a soffitto, a parete o su binario, è caratterizzato da un connubio di precisione e forza. Il proiettore professionale, dalle alte prestazioni, completamente orientabile a 360° in orizzontale e in verticale, è studiato per avere il minimo impatto visivo.

*A punctual point of view able to emphasize details and exclusive spaces: ML, installable on ceilings, walls or rail, is characterized by a combination of precision and strength. The professional projector, capable of high performances, completely orientable up to 360° both horizontally and vertically, is designed for having a minimal visual impact.*



## CODE COMPOSITION

1014	2	E	ND	
				<i>light colour</i>
		<b>27</b>		2700K
		<b>30</b>		3000K
		<b>40</b>		4000K
				<i>lens</i>
		<b>24</b>		24°
		<b>38</b>		38°
				<i>installation</i>
		<b>S</b>		surface
		<b>T</b>		track
				<i>finishing</i>
		<b>WH</b>		white
		<b>BL</b>		black

example of code composition 1014 **WH 2 S 24 E 30** ND

## TECHNICAL FEATURES

<b>Code</b>	<b>1014</b>
<b>Type</b>	Projector +/- 360° 
<b>Material</b>	Aluminum
<b>Finishing</b>	White   Black
<b>Weight</b>	1.2 Kg
<b>Mounting</b>	Wall and ceiling
<b>IP rating</b>	IP40
<b>Insulation class</b>	III
<b>Control gear</b>	Constant current electronic driver on board
<b>Cut out for plasterboard</b>	-
<b>Lamp type</b>	LED 700 mA 
<b>Lamp wattage</b>	1 x 26W
<b>Luminous efficacy</b>	133 lm/W - 3000K
<b>Light distribution</b>	Beam 24° Beam 38° (on request)
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K White 2700K   4000K (on request)
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>80 >90 (on request)
<b>Emergency</b>	On request
<b>Energy efficiency class</b>	A++
<b>Note</b>	On request available dimmable PUSH or DALI.



