PANZERI

Willy Glass


220-240V AC dimmable (DALI/Push DIM) L07631.060.0402


Data sheet

| CODE | L07631.060.0402 |
|--------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 40W |
| EFFICACY | 89.68lm/W |
| LIGHT SOURCE | LED |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 4592lm |
| LUMEN OUTPUT | 3587lm |
| EFFICIENCY | 78.1% |
| WEIGHT | 8,38 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 69,0 x 69,0 x 53,0 cm |



Technical drawing









Suspension lighting fixture for interiors, with direct light emission. Turned pickled sheet metal structure in metallized grey polyacrylic paint. Extruded aluminium heat sink. Lampshade in black decorated blown glass. Diffuser in modelled frosted glass. 2m (78,7") long steel suspension cables. 2,2m (86,6") long power cable in transparent PVC. Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in metallized grey polyacrylic paint.