


# 206003

# HYDROFLOOR MAXI INVISA

### ALL BLACK APPEARANCE.

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket, non-visible stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 16 CREE XP-G2 LED + special optics with "invisa-light" technology. IP67 rating.





light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led	V	15°	2.232	82.67
high-power led	V :	35°	2.120	78.52
high-power led	V :	55°	2.014	74.59
4000°K neutral-white				
high-power led		15°	2.325	86.11
high-power led	V :	35°	2.208	81.78
high-power led		55°	2.098	77.69

#### Finish color options:





## **Technical features**


















#### **Technical data**

Wattage	27 WATT		
IP Rating	IP67		
IK Rating	IK10		
Material	High corrosion resistance die-cast copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Trim	Stainless steel AISI 304		
Light source	NR. 16 x 1.5W CREE "XP-G2" LED		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Screws	Stainless steel		
Optics	Special optics with "invisa-light" technology		
Gasket	Silicone rubber		
Glass	Tempered		
Cable	Double M20 cable gland		
Static weight resistance	Max 5000 Kg		
Power cable	1 mt. neoprene power cable included		
Gross weight	4,50 Kg		
Included	Polypropilene housing for recess included		



Stainless steel finish trim available on request



Sliding hooking system for recessing box

