## **PANZERI**

### Two

#### 220-240V AC ON-OFF

L03821.000.0406





#### Data sheet

CODE	L03821.000.0406
SYSTEM POWER CONSUMPTION	10W
EFFICACY	59.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	850lm
LUMEN OUTPUT	595lm
EFFICIENCY	70%
WEIGHT	1,63 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	18,0 x 46,0 x 20,0 cm



Suspension lighting fixture for interiors, with direct light emission.

 $\label{prop:eq:extruded} \textbf{Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint, or }$ with gold leaf coating.

Pickled sheet metal end cap in white, black, bronze, mat brass or gold polyacrylic paint.

Aluminium dissipation plate. Flat frosted glass diffuser.

 $\label{lem:pickled} \mbox{Pickled sheet metal frame in white, black, bronze or mat brass polyacrylic paint, or with}$ gold leaf coating.


 $2m\,(78,\!7")$  long suspension and power cable in transparent PVC.

Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal  $% \left( 1\right) =\left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right$ covering in white, black, bronze or mat brass polyacrylic paint, or with gold leaf coating.






#### **Technical drawing**



#### Polar diagram



# **PANZERI**

### Two

#### Accessories / dimming

XM14/230

Dimmable device for 230V LED modules, 5÷100W.



