PANZERI

Planet Ring

220-240V AC dimmable (DALI/Push DIM)

P08301.100.0402





Data sheet

| CODE | P08301.100.0402 |
|----------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 142W |
| EFFICACY | 82.58lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B20) 80.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 17714lm |
| LUMEN OUTPUT | 11727lm |
| EFFICIENCY | 66.2% |
| WEIGHT | 13,64 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| GLOW WIRE TEST PERFORMANCE | 850° |
| PACKING DIMENSIONS | 106,0 x 106,0 x 18,0 cm |
| | |



Ceiling lighting fixture for interiors, with direct light emission. Pickled sheet metal structure in white polyacrylic paint. Aluminium dissipation plate.


Pickled sheet metal closing frame in polyacrylic paint. Modelled polycarbonate diffuser with opaline finish.







Technical drawing



Application



Polar diagram

