# ASCOLI RECESSED 6149
## SKU 1286021

astro



## PRODUCT SPECIFICATION

### GENERAL

| | | | |
|---|---|---|---|
| FINISH: | White | CABLE LENGTH: | 200mm |
| MAIN MATERIAL: | Metal - Mild Steel | GROSS WEIGHT: | 0.55 (Kg) |
| DIMENSIONS: | H:128mm  W:21mm  DIA: 80mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Ceiling Mount - (Plaster board installation only. Not suitable for mounting in a solid ceiling) | IP RATING: | IP20 |
| | | BATHROOM ZONE: | Zone 3 |
| CUT OUT HOLE: | 44mm/1-3/4" | VOLTAGE: | Mains 230 (V) |
| RECESS DEPTH: | 30mm | PRODUCT F MARK: | Suitable for mounting on flammable materials |
| FIRE RATING: | Not Applicable | | |

### LAMP

| | | | |
|---|---|---|---|
| LIGHT SOURCE: | GU10 | MACADAM ELLIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | 50W Max | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | 57mm | BEAM ANGLE: | Lamp Dependent |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | 90 (Degrees) |
| LUMINOUS FLUX: | Lamp Dependent | ROTATION ADJUSTMENT ANGLE: | 330 (Degrees) |
| COLOUR TEMP: | Lamp Dependent | AVERAGE LIFESPAN: | Lamp Dependent |
| CRI: | Lamp Dependent | L70: | Not Applicable |
| R9: | Lamp Dependent | | |

### ELECTRICAL

| | | | |
|---|---|---|---|
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER/BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Lamp Dependent | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Lamp Dependent |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER/BALLAST INCLUDED? | Not Applicable |

## ADDITIONAL INFORMATION

CE



BOX QUANTITY X12

Ø57

Ø80

21

128 MAX

Ø90

330Å

Ø44 CUTOUT